
Cast Simplex Strainers

BFH125 - Ductile Iron

Quick Open Swivel Clamp Cover

The Sure Flow model BFH125 Basket Strainers are a High Capacity design featuring Class 125 ASME Flanged end connections and top removal of the screen. The screen is



in the form of a basket, with a lifting handle, so that all particulate captured and retained by the screen can be easily removed for disposal. They are intended for applications where larger amounts of solid particulate are expected, and where clean-out will be frequent. Models are standard with a bolted "Swivel Clamp Cover" to allow fast and easy screen removal.

Notes:

Must specify if for steam service

Manufacturer reserves the right to modify dimensions, materials, or design. Consult factory for certification.

Construction

Ductile Iron - Body, Cover - ASTM A536 Class 65-45-12 BUNA-N - Cover O-Ring All screens are Stainless Steel

Operating Pressures and Temperatures

Size

2" - 6"

Standard Screens

Standard

3/64" perf

1/8" perf

psi @ Temp WOG

150 @ 150 °F

Opening

0.045"

0.125"

23

Dimensions (Inches)									
Si Inches	ze Prefix	А	В	С	D	Blow Off NPT	Basket Removal Clearance	Shipping Weight (LBS)	
2	0200	10 1/2	4 1/4	7 5/8	11 13/16	1	8 3/4	59	
3	0300	13 1/8	4 15/16	10 5/8	15 13/16	1	11 11/16	101	
4	0400	16 3/4	6 5/16	10 3/4	17 1/16	1	12	197	
6	0600	19 5/8	7 1/2	18 3/8	26	1	19 3/8	362	

Ordering Information								
Example: Include full description								
Size	Model	Screen						
(Prefix)	Number	Opening						
0200	BFH125	045						

2" Basket Strainer, Cast Iron, Class 125 ASME Flanges, 3/64" Perf Screen



Toll Free: 1-800-263-8251 Toll Free Fax: 1-800-876-1164 International: 1-905-335-1350 International Fax: 1-905-332-4993 Email: info@sureflowequipment.com www.sureflowequipment.com

Type BFH125

Size

2" - 3"

4" - 6"